

1. DESCRIPTION

Impa Pink Wood SB Primer is a oleo resinous pink coloured penetrating primer for interior and exterior wood. It may serve as primer underneath Universal Undercoat.

2. FEATURES

- Easy and direct application as supplied.
- Applications by brush to ensure proper penetration into wood surface.
- Oil-base wood primer for interior and exterior applications
- It is designed specifically for use on interior and exterior new and unpainted hard and soft wood before applying a paint topcoat.
- Also used on wooden chip board surfaces.
- Slow-drying- provides excellent penetration and sealing properties on wood and provides a good bond for subsequent coats of paint

3. LIMITATIONS

- Not recommended for surfaces other than wood
- To prevent moisture penetration, ensure that the end gains of the timber are adequately primed.
- Do not apply on previously painted/varnished wood in good condition
- Must be over coated within 4 days when used outside to avoid intercoat adhesion problems.

4. SURFACE PREPARATION

- Clean surfaces with **Removal Simple Wash** to remove dirt, mildew and other contaminants.
- All nail heads must be spot primed with **Impa Zinc Phosphate Primer** prior to priming the wood to prevent corrosion and staining.
- Repair damaged wood with **Restore Wood Putty**
- **New Wood:** Sand wood in the direction of the grain to a smooth finish, dust off thoroughly. Seals knots with **Impa Knot Seal**. Apply primer and allow to dry.
- **Previously painted wood in poor condition:** Remove old paint/varnish with **Restore Deep Penetrating Paint Stripper** or by scraping and sanding. Prepare as for new wood.
- **Grey weathered wood:** Restore grey weathered wood by using **RESTORE WOOD RESTORDER**. Rinse, allow to dry and prime.
- **Oiled wood:** Sand surface in the direction of the grain back to the original wood, dust off and prime.

SOLVENTBASE PRIMER

IMPA PINK WOOD SB PRIMER

ISSUED DATE: JUNE 2014 Rev 1

TECHNICAL DATA

<i>Product Code</i>	<i>PI2014</i>
<i>Colour</i>	<i>Pink</i>
<i>Appearance</i>	<i>Low Sheen</i>
<i>Shelf life</i>	<i>12 Months</i>
<i>Packaging</i>	<i>500ml, 1L&5L (20L on request)</i>
<i>Flashpoint</i>	<i>37°C</i>
<i>Viscosity</i>	<i>70 - 75KU @23°C</i>
<i>S.G (weight)</i>	<i>1,32 – 1,35kg/L</i>
<i>Solids per volume</i>	<i>57– 59%</i>
<i>Solids per mass</i>	<i>75– 77%</i>
<i>Practical Spreading rate (depending on porosity)</i>	<i>8-10m²/L @ 35µm, DFT</i>
<i>Recommended finishing coats.</i>	<i>1</i>
DRYING TIME	
<i>Touch dry time</i>	<i>6 Hours at 23°C</i>
<i>Recoating Time</i>	<i>18 Hours at 23°C</i>
<i>Full Cure</i>	<i>4-7 Days</i>
APPLICATION	
<i>Roller & Brush</i>	<i>Ready for use (Mohair roller)</i>
<i>Spray</i>	<i>Dilute with Mineral Turpentine</i>
<i>Cleaning</i>	<i>Mineral Turpentine</i>
<i>Mixing</i>	<i>Stir until homogeneous</i>
	<i>Stir occasionally during use</i>

5. APPLICATION

- Ready for use by brush or roller.
- Apply a full even coat and allow to dry for 18 hours before overpainting.

6. PRECAUTIONS.

- Application should be avoided in cold and moist weather conditions.
- **Do Not** apply the product at surface temperatures below 6°C (minimum of 2°C above dew point) and temperatures above 40°C
- **Do Not** apply if ambient temperature is less than 10°C or more than 40°C.
- **Do Not** apply if relative humidity temperature is less than 10°C or more than 85. °C
- Always keep paint out of reach of children
- Ensure good ventilation during application and drying
- If accidental contact with skin should occur, wash immediately with soap and water or a recognized skin cleaner.
- Take care to avoid contact with the eyes.
- In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
- Harmful if swallowed. Seek medical attention and do not induce vomiting
- Do not smoke while painting
- Flammable. Store in a cool dry place away from heat and sparks
- Refer to Material Safety Data Sheet for complete information.

Environmental Health & Safety Information

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: LOW & HIGH AROMATIC SOLVENTS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapours and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN AND ANIMALS - DO NOT TAKE INTERNALLY.

Refer to Material Safety Data Sheet for additional health and safety information.

IN CASE OF FIRE: Use foam, CO₂, dry chemical, or water fog.

SPILL – Absorb with inert material and dispose of as specified under **Thinning/Clean-up**.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust.

DISCLAIMER

The technical information contained in this document are given in good faith and are meant to be used as a guideline by the specifier or user. Whilst we are confident about the quality of our products, we cannot accept any liability for the incorrect use or application of our products. Surface preparation forms an integral part of the scope of works and it is expected that the highest standards are maintained during surface preparation and application, to ensure that our products perform as intended. Always ensure to use the same product batch numbers, refrain from doing spot touch-ups and paint surfaces from corner to corner to prevent colour and sheen variance. As technology may change over time we reserve the right to change products to keep up with changes in raw materials or product trends without pre notice. Although we will always privail to keep clients informed about changes to be made, but cannot bind ourself to such notes Please ensure the use of the latest Technical Data Sheet.

Please note : that all our latest Product Data Sheets and Material Safety Data Sheets are available for viewing on our website at www.impa.co.za. All information listed is owned or used under licence of Impa Paints and its related companies. © 2010 Lurama 149 (Pty) Ltd. All rights is reserved.